



X-STRESS 2106G

X-STRESS, White, 13-Gauge Nylon Shell, Gray Flat Nitrile Palm Coating



Key Features & Benefits:

- Lightweight, comfortable, breathable and built for all day wear.
- Flat Nitrile coatings are highly impermeable to liquids and provide a premium dry grip for specific applications that require secure holding power.
- Palm is resistant to chemicals, water and ultraviolet light.
- Elastic Knit Wrist helps prevent dirt and debris from entering the glove.


ANSI/ISEA 105



EN 388



4121

Applications:		Industries:	Certifications/Ratings:
<ul style="list-style-type: none"> • Fastening • Parts & Material Assembly • Maintenance & Repair • Parts Cleaning 		<ul style="list-style-type: none"> • Automotive • Electronics • Janitorial • Metal Fabrication • Plumbing/HVAC 	<p>ANSI ISEA-105</p> <ul style="list-style-type: none"> • Cut Level- N/R • Abrasion Level- 3 • Puncture Level- 2 <hr/> <p>ANSI ISEA-138</p> <ul style="list-style-type: none"> Impact Level- NR
Ordering:		Composition	Additional Information
<ul style="list-style-type: none"> • Unit of Sale- 1 DZ • Case pack- 12 DZ • Country of Origin- China • Available Sizes- S-XL 	<ul style="list-style-type: none"> • 13 Gauge, 45% Nylon, 2% Elastic Shell. • 53% Flat Nitrile • Knitwrist 	<p>Wash using warm water and commercial laundry detergent. Water temperature not to exceed 122°F/ 50°C. Air-dry or tumble-dry with no heat</p> <hr/> <p> Warning: Cancer & Reproductive Harm- www.P65Warnings.ca.gov</p>	

PACKAGING SPECIFICATIONS

ITEM# 2106G



X-STRESS 2106G

X-STRESS, White, 13-Gauge Nylon Shell, Gray Flat Nitrile Palm Coating

Packaging Dimensions

Item Number	Item Number UPC	Inner UPC	Case UPC	Case L (In)	Case W (In)	Case H (In)	Weight (lbs)
2106GS	196852107285		50196852107280	18.90	10.63	10.24	13.23
2106GM	196852107292		50196852107297	18.90	10.63	10.24	13.91
2106GL	196852107308		50196852107303	18.90	10.63	10.24	14.86
2106GXL	196852107315		50196852107310	18.90	10.63	10.24	15.81



www.C2VPPE.com