



by Honeywell



## 4178 CL Face Shield Window

(Face shield bracket sold separately)

<b>Description</b>	High performance wide vision <i>clear</i> window. Injection molded propionate. For use on F400/F500 series of face shield brackets, FM70/FM71 dielectric cap peak mounting brackets and FH66 aluminum cap peak mounting bracket.
<b>Window Size</b>	8" x 16 ½ " x .060 mm (does not have universal hole pattern)
<b>Material</b>	Propionate
<b>Visible Light Transfer (VLT)</b>	85.0%
<b>Headgear Style</b>	N/A
<b>Replacement Headgear Available</b>	No
<b>Compatible Face Shields</b>	F400 (all series), F500 (all series) , FM70, FM71, FH66
<b>Replacement Sweatband</b>	No
<b>Hardhat Options (Yes/No)</b>	No
<b>Other Available Colors</b>	Clear, Dark Green,IRUV3, IR/UV5, IR/UV8, TV Grey
<b>Dielectric Frame</b>	N/A
<b>Standards Passed</b>	ANSI Z87.1; CSA Z94.3
<b>Packaging</b>	12/Box; 72 ea/Case (Note - also available in bulk 50/box)
<b>Country of Origin</b>	USA
<b>Unit Weight</b>	.40 lbs.
<b>Case Weight</b>	29 lbs.
<b>Case Dimensions</b>	23.5 x 22.5 x 8.8
<b>MSDS Requirements</b>	None required
<b>Harmonization Code</b>	6506.10.6075

WARNING: This reference manual provides only an overview of the products shown. It does not provide important product warnings and instructions. Sperian Protection recommends that all users of its products undergo thorough training and that all warnings and instructions provided with the products be thoroughly read and understood prior to product use. It is necessary to assess hazards in the work environment and to match the appropriate personal protective equipment to particular hazards that may exist. A complete and thorough hazard assessment must be conducted to properly identify the appropriate personal protective equipment to be used in a particular work environment. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS AND TO PROPERLY PERFORM A HAZARD ASSESSMENT MAY RESULT IN SERIOUS PERSONAL INJURY, ILLNESS OR DEATH.



by Honeywell

## Technical Specifications