



R3 CONCRETE ANCHOR

RAPID • RIGID • REUSABLE



EXCLUSIVE INNOVATION

INSTALLS IN SECONDS,
LASTS A LIFETIME

- Simple, safe, and secure one-hand operation for easy installation and removal
- Rigid stainless steel tri-wedge design and diamond hard coating
- Cycle tested up to 5000 uses and beyond

Omni-directional D-Ring rotates to mitigate connector rollout



See the Video



Now available at goSafe.com
Call 800.330.9240 or email Sales@goSafe.com





Horizontal, Vertical or Overhead Applications

Omni-Directional D-Ring Mitigates Connector Rollout

Quick Release Button

Reusable: Cycle tested beyond 5000 uses

Diamond Hard Coating

Rigid Tri-Wedge Design

Designed to work for years in the toughest conditions.

The new Werner R3 Concrete Anchor is a reusable, safe and secure anchorage solution for horizontal, vertical or overhead anchoring applications.

- A rapid quick release button allows users to install and remove with speed, boosting productivity.
- Built with a rigid tri-wedge design and diamond hard coating, provides incredible durability and corrosion-resistant performance in harsh environments.
- The anchor incorporates a revolutionary omni-directional design that allows the connector to swivel and hinges in any direction to mitigate connector rollout.

Unlike traditional designs, the Werner R3 never requires a tool for removal.



See the Video



ANSI Z359.18 Type A
 OSHA 29 CFR 1926.502 & 1910.140

SPECIFICATIONS

MODEL NO.	MATERIAL	LENGTH	WIDTH	CONNECTION SIZE	MINIMUM BREAKING STRENGTH (MBS)	APPROX. WEIGHT	COMPLIANCE STANDARDS
A510300	Stainless Steel Nylon	7.5 in (19.1 cm)	2.68 in (6.8 cm)	2 in (5.1 cm)	5,000 lb (22.2kN)	0.70 lb (0.35 kg)	ANSI Z359.18-2017 Type A OSHA 1910 & 1926